



Bair Hugger® Therapy Temperature Management Unit

Model 775



Quiet. Adjustable. Safe. Effective.
It's everything you want from your forced-air warming unit...and more.



Quiet, adjustable warming options for all Bair Hugger® blanket styles



Arizant Healthcare introduced forced-air warming to the world in 1987 with the launch of Bair Hugger therapy. Since that time, our Bair Hugger warming units and blankets have safely and effectively warmed more than 110 million patients.

Our latest advancement in forced-air warming – **the Bair Hugger Model 775 temperature management unit** – is the future gold standard in patient warming. It offers adjustable airflow, precise temperature delivery and ease of use from a single, quiet warming unit.

Two airflow settings and hose-end temperature sensing ensure precise temperature delivery and compatibility with all Bair Hugger blanket styles – pediatric to adult.

Three temperature sensors and adjustable airflow provide safe, quick temperature response and greater heat transfer.

The Model 775 can track and report forced-air warming therapy duration, over-temperature information, calibration, built-in hour meter and fault codes all via the front panel – no need to open the unit.

Accessories for the Model 775 warming unit allow the unit to be mounted on a hard surface, an IV pole, bed rail or rolling cart.



©2009 Arizant Healthcare Inc. All rights reserved.
10393 West 70th Street, Eden Prairie, MN 55344 USA
tel 952-947-1200 | 800-733-7775
fax 952-947-1400 | 800-775-0002
web arizanthealthcare.com | bairhugger.com

Bair Hugger, Arizant, Arizant Healthcare and the Bair Hugger and Arizant logos are trademarks of Arizant Healthcare Inc. registered in the U.S. Patent & Trademark Office.

603032B 7/09

Specifications

Dimensions

13'h x 14"w x 13"d (33h x 35w x 33d cm)

Weight

16 lb (7.3 kg)

Operating Temperatures

High: $43^{\circ} \pm 1.5^{\circ}\text{C}$ ($109.4^{\circ} \pm 2.7^{\circ}\text{F}$)

Med: $38^{\circ} \pm 1.5^{\circ}\text{C}$ ($100.4^{\circ} \pm 2.7^{\circ}\text{F}$)

Low: $32^{\circ} \pm 1.5^{\circ}\text{C}$ ($89.6^{\circ} \pm 2.7^{\circ}\text{F}$)

Fan Speeds and Relative Noise

High Fan Setting: 37 CFM (53 dBA)

Low Fan Setting: 32 CFM (48 dBA)

Leakage Current

Meets UL 60601-1 and IEC 60601-1 requirements.

EN 60601-1-2; CAN/CSA-C22.2,

No. 601.1, EN 55011; ASTM F2196-02

Safety Systems:

Audible and visual alarms;

Over-temperature $\leq 56^{\circ}\text{C}$, $53^{\circ}\text{C} \pm 3^{\circ}\text{C}$ typical

Filter

High-efficiency 0.2 μm filter

Device Ratings

110-120 VAC, 50/60 Hz, 11.7 Amperes

220-240 VAC, 50/60 Hz, 7.2 Amperes

100 VAC, 50/60 Hz, 14.5 Amperes

Ordering Information

Bair Hugger Model 775 Temperature Management Unit

To order, please contact your Arizant Healthcare Inc. representative or call 1-800-733-7775.